



PUNCTURE FREE "ON ROAD" TYRE SEALANT- Tyre Size Chart.

LIGHT DUTY TRUCKS, HEAVY TRUCKS, TRAILERS & BUSES (over 1.5 tons).

Section 1: On Road Trailers : Trailer Tyres suitable for Highway Use, fitted to Trailers & Powered Vehicles other than Passenger Cars. For "On Road" use trailers with rims sizes in excess of 12 inches, refer to Auto's and Car Chart.

TRAILERS:

Rim Size	OKO	Rim size	OKO	Rim Size	OKO
8 Inch Rims.	MLS		MLS		MLS
4.00. 8	200	9 Inch Rims		12 Inch Rims	
4.50. 8	200	6.00. 9	250	4.80. 12	200
4.80. 8	200	6.90. 9	250	5.30. 12	225
5.00. 8	200	21 x 8.00. 9	275	5.60. 12	225
5.30. 8	200			6.00. 12	225
5.70. 8	200	10 Inch Rims		7.00. 12	250
15 x 4.50. 8	200	6.50. 10	300	145R. 12	250
16.5 x 6.50. 8	250	7.50. 10	350	155R. 12	250
16 x 6.00. 8	250	20.5 x 8. 10	275	155/70. 12	250
16 x 6.5. 8	250	23.00 x 9.00. 10	350	23.5 x 8.5. 12	300
18.5 x 8.5. 8	250			27.0 x 10.0. 12	350
18.5 x9.5. 8	275				
18 x 7.00. 8	200				

Section 2: HEAVY TRUCKS, VANS & BUSES

Rim Size	OKO	Rim Size	OKO	Rim Size	OKO
15 Inch Rims	MLS	15 Inch Rims	MLS	15 Inch Rims	MLS
6.70R. 15LT	600	185. 15	700	215/75R	900
7.00R. 15LT	600	205/70. 15	800	235/75R	900
7.50 15	700	205/80. 15	800	255/75R	1000
7.50R . 15TR	700	225/75. 15	900		
7.75. 15ST	800	30x9.50R. 15LT	800	16 Inch Rims	
8.25R. 15TR	800	31x10.50R. 15Lt	900	6.00. 16	500
9.00R. 15TR	900	31x11.50R. 15LT	1000	6.50R. 16Lt	600
10.00R. 15TR	1000	32x11.50R. 15Lt	1000	7.00. 16	700
11.00R. 15TR	1100	33x12.50R. 15LT	1200	7.50R. 16Lt	900
12.00. 15	1200	LT195/75R. 15	800	8.25. 16	1000
		LT205/75R. 15	900	8.25R. 16	1000

Section 2: HEAVY TRUCKS, VANS & BUSES **Continued/.....**

Rim Size	OKO	Rim Size	OKO	Rim Size	OKO
16 Inch Rims	MLS	17.5 Inch Rims	MLS	19.5 Inch Rims	MLS
8.35. 16	1100	7.00. 17.5	1100	265/70. 19.5	1800
9.00. 16	1200	8.00. 17.5	1300	285/70. 19.5	2000
195. 16	900	8.50. 17.5	1400	305/70. 19.5	2200
195/75. 16	900	9.00. 17.5	1500		
205. 16	1000	9.50. 17.5	1500	20 Inch Rims	
205/75. 16	1100	10.00. 17.5	1600	6.50. 20	1200
215. 16	1100	11.00. 17.5	1800	7.00. 20	1400
215/75. 16	1100	14.00. 17.5	2400	7.50. 20	1400
225/75. 16	1200	205/75. 17.5	1300	7.50R. 20	1400
245. 16	1200	215/75. 17.5	1400	8.25. 20	1600
10.50. 16	1300	225/75. 17.5	1500	9.00. 20	1800
11.00. 16	1600	235/75. 17.5	1500	10.00. 20	2000
14.00. 16	2100			10.50. 20	2200
LT215/85R. 16	1100	18 Inch Rims		11.00. 20	2400
LT225/75R. 16	1200	7.00. 18	1000	12.00. 20	2400
LT235/85R. 16	1200	7.50R. 18	1200	12.00/80. 20	2400
LT245/75R. 16	1200	9.00. 18	1500	12.00R. 20	2400
LT255/85R. 16	1200	10.00. 18	1700	12.50. 20	2400
LT265/75R. 16	1300	10.50. 18	1800	13.00. 20	2600
LT285/75R. 16	1500	12.50. 18	2100	13.00/80. 20	2600
		14.00. 18	2500	13.00R. 20	2600
16.5 Inch Rims				14.00. 20	2800
8.00. 17	1200	19.5 Inch Rims		14.00/80. 20	2800
8.75. 17	1300	7.00. 19.5	1200	14.00R/20. 20	2800
9.50. 17	1300	8R. 19.5	1500	14.00R. 20ML	2800
10.00. 17	1400	9.00. 19.5	1600	14.50. 20	2900
12.00. 17	1800	9.50. 19.5	1600	14.75. 20	2900
		10.00. 19.5	1800	15.00. 20	3000
17 Inch Rims		15.00. 19.5	2800	15.50/80. 20	3100
7.00. 17	1000	15R. 19.5	2800	16.00. 20	3200
7.50. 17	1000	16.00. 19.5	3000	16.00R. 20	3200
8.00. 17	1200	16.5R. 19.5	3000	365 /80. 20	3000
8.25. 17	1300	18.00. 19.5	3600	405/75. 20	3200
8.75. 17	1400	18R. 19.5	3600		
9.50. 17	1400	19.50. 19.5	3800	20.5" RIMS	
10.00. 17	1500	19.5R. 19.5	3800	525/65. 20.5	4000
12.00. 17	1900	245/70. 19.5	1600	615/65. 20.5	4000
		255/70. 19.5	1800		

Section 2: HEAVY TRUCKS, VANS & BUSES **Continued/.....**

Rim Size	OKO	Rim Size	OKO	Rim Size	OKO
-----------------	------------	-----------------	------------	-----------------	------------

21Inch Rims			22.5 Inch Rims					MLS
12.00. 21		2500	345/75. 22.5		3200			
14.00R. 21MI		3000	365/70. 22.5		3200			
			385/65. 22.5		3400			
22Inch Rims			385/80. 22.5		3400			
9.00. 22		2000	425/65. 22.5		3600			
10.00R. 22		2200	445/65. 22.5		4000			
11.00. 22		2600						
11.00R. 22		2600	24 Inch Rims					
			9.00. 24		2000			
22.5 Inch Rims			10.00. 24		2400			
8.00R. 22.5		1800	11.00R. 24		2800			
9.00R. 22.5		2000	12.00R. 24		3000			
10.00R. 22.5		2200	13.00R. 24ML		3400			
11.00/70. 22.5		2600	14.00R. 24ML		3400			
11.00R. 22.5		2600	14.00R. 24		3400			
12.00/70. 22.5		2800	14.00/80. 24		3400			
12.00R. 22.5		2800	405/70. 24		4000			
12.50. 22.5		2800						
12.75. 22.5		3000	24.5 Inch Rims					
13.00. 22.5		3200	11.00. 24.5		2800			
13.00R. 22.5		3200	12.00. 24.5		3000			
15.00R. 22.5		3400	13.50. 24.5		3400			
16.50. 22.5		3800	275/80. 24.5		2800			
16.5R. 22.5		3800	285/75R. 24.5		2800			
18.00. 22.5		4000	295/80. 24.5		3000			
18.00R. 22.5		4000	305/75. 24.5		3000			
235/80. 22.5		2000	315/75. 24.5		3200			
245/75R. 22.5		2200						
255/70. 22.5		2200	25 Inch Rims					
255/80. 22.5		2200	11.00. 25		3000			
265/75R. 22.5		2200	12.00. 25		3200			
275/70. 22.5		2500	14.00R. 25ML		3800			
275/80. 22.5		2500						
295/75R. 22.5		2800						
295/80. 22.5		2800						
315/70. 22.5		2800						
315/75. 22.5		2800						
315/80. 22.5		2800						